PO Box 2891



	VEOLIA
V	VCOCIA

			Point BC NSW 2									
Pollutant	Units of measure	Monitoring frequency required by licence	No. of times measured during month	Annual Limits		Min.	10%-ile	Median	Average	90%-ile	Max.	Comments / explanation
PL 12904				10%-ile Limit	90%-ile Limit							
Ionitoring Poin	t 8											
Conductivity	microsiemens per centimetre	Continuous during discharge	Continuous during discharge	-	-	54,648	74,038	75,382	75,371	76,566	80,300	
emperature	celsius	Continuous during discharge	Continuous during discharge	-	-	17.84	18.95	20.28	20.44	22.17	24.35	
Salinity	_	Continuous during discharge	Continuous during discharge	-	72	40.19	55.24	58.19	58.09	60.86	63.47	
Oxidation Reduction Potential	millivolts	Continuous during discharge	Continuous during discharge	-	-	209.96	248.34	304.11	306.73	374.39	398.50	
bH	рН	Continuous during discharge	Continuous during discharge	6.5	8.8	6.97	7.10	7.18	7.17	7.24	7.36	
Fotal dissolved solids	milligrams per litre	Weekly during any discharge	4	-	-	58,200	58,740	61,050	60,650	62,240	62,300	
otal residual chlorine	milligrams per litre	Daily during any discharge	31	-	0.1	0.04	0.04	0.04	0.04	0.04	0.06	
otal suspended solids	milligrams per litre	Weekly during any discharge	4	-	30	2.00	2.60	5.00	5.25	8.10	9.00	
Γurbidity	nephelometric turbidity units	Daily during any discharge	31	-	-	0.20	0.20	0.20	0.25	0.40	0.60	

Note 1: The table above is analysing the monthly data against annual limits. A table that analyses the annual data against the annual limits prescribed above will be published in January of each year.
*: SWDN- Sydney Water Distribution Network

Published:

2024Jan04